

# Denso Skid Resistant Overbanding Tape

A cold applied skid resistant bituminous tape for sealing of pavement cracks

## Composition

Denso Skid Resistant Overbanding Tape is a thick, polymer modified bituminous adhesive layer with a rubber based backing in tape form with a disposable release film.

## Uses

Denso Skid Resistant Overbanding Tape is used for surface sealing of cracks or failed reinstatement joints up to 5 mm wide in road pavements on secondary roads. Once applied, the tape provides a skid resistant surface.

## Characteristics

Denso Skid Resistant Overbanding Tape;

- has excellent resistance to water, acids, alkalis and salts,
- prevents further cracking and spalling of the road surface, and
- has a skid resistant surface.

## Application

See *Instructions for use* for details. Denso Skid Resistant Overbanding Tape is suitable for both hand and machine application. For machine application Denso roller 75 applicator is recommended.

Recommended primer: Densoband Primer

Application Temperature: +8°C to +45°C.

## Availability

Denso Skid Resistant Overbanding Tape is available in 10 m lengths with a 30 mm or 40 mm width. Rolls per carton;  
30 mm width – 10 rolls  
40 mm width – 8 rolls

## Storage Conditions

Store in a cool and dry place in original packaging.

## Waste Material

Please avoid or minimise waste wherever possible. Please do not discard waste material, including packaging, in the surrounding environment. Follow all relevant legislation for disposal.

## Typical Properties

Colour	Black
Thickness	2.8 mm
Core Size	76 mm I.D.
Softening point	120°C
Skid Resistance (TRL Road Note 27)	Dry 67 Wet 66 Exceeds Dept for Transport Requirement

Important: Winn & Coales (Denso) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request. Winn & Coales (Denso) Ltd operate a Quality Management System registered to BS EN ISO 9001 (BSI Certificate no. FM01548) and an Environmental Management System registered to BS EN 14001 (BSI Certificate 583748).