



## **Kesfloor WB Sealer**

### **DESCRIPTION**

KESFLOOR WB SEALER is a water dispersable epoxy primer/sealer having excellent adhesion to concrete. Can be applied to newly laid, damp or dry mature concrete.

Anti-slip aggregate is also available, for use where a slip resistant surface is required. Please call our technical department for more information.

### **ADVANTAGES**

Low odour - ideal for food processing areas. Good penetration properties because of its low viscosity. Easy to apply. Low cost. Improves chemical resistance of concrete  
Excellent adhesion to many types of substrate.

### **USES**

KESFLOOR WB SEALER is ideal for warehouses, food processing areas etc. Ideal as curing membrane for concrete.

### **TECHNICAL DATA**

S.G. (at 15.5°C)	1.06
Solids by weight	56%
Film Thickness (dft)	110 microns @ 5 sq.m. per litre
Pot Life (at 20°C)	1.5 hours
Application Temperature	5°C to 30°C
Overcoating interval	24 hours maximum (at 20°C)
Initial Hardness (at 20°C)	24 hours
Full cure	7 days
Recommended No. of coats	2

### **SURFACE PREPARATION**

Substrates should be free from all types of contamination i.e. dirt, grease, oils, fats and laitence. Cleaning should preferably be by shot blasting or mechanical abrading or by controlled hot compressed air.

### **MIXING AND APPLICATION**

The KESFLOOR WB SEALER part A resin should be added to the part B hardener, taking care to remove all the resin from the container and mix for at least 2 minutes until completely homogeneous.

Apply the KESFLOOR WB SEALER to the prepared substrate by brush or roller ensuring a continuous film. Avoid puddles and over application. Very porous surfaces may require two coats. Tools can be cleaned with water.

### **COVERAGE**

Theoretical coverage is 5 sq.m per litre depending on the substrate.

### **PACKAGING**

KESFLOOR WB SEALER is supplied in 5 litre units.

### **Colours**

Green, Red, Grey. (Other colours can be made to order).

### **STORAGE**

Store between 5°C and 30°C

### **HEALTH AND SAFETY (see separate health and safety data sheet)**

Wear gloves and protective clothing when using KESFLOOR WB SEALER. A suitable barrier cream is also recommended. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, was immediately with soap and water.

### **WARRANTY DISCLAIMER**

The technical data herein has been compiled for your help and guidance and is based upon our experience. As we have no control over the use to which our information is put, no warranty, expressed or implied is intended or given and we cannot be held responsible for coverage, performance or any damages incurred.

Kestral Construction Products Ltd, Brindley Road, St. Helens, WA9 4HY
--

DATA S/781998
---------------