


# Roundex®

Non crosslinked PE foam backer rod for cold sealing applications (up to +80°C).

DIN18450 & ASTM C1330. compliant



Reference	Presentation	Meters/ box	Diameter A (mm)	Density (kg/m <sup>3</sup> )
Roundex 6	Roll	2500±100	6±1	23±5
Roundex 8	Roll	1500±60	8±1	23±5
Roundex 10	Roll	1150±45	10±1	23±5
Roundex 13	Roll	750±30	13±1	23±5
Roundex 15	Roll	550±25	15±1	23±5
Roundex 20	Roll	350±15	20±1	23±5
Roundex 25	Roll	200±8	25±1	23±5
Roundex 30	Roll	160±8	30±1,5	23±5
Roundex 40	2m±4cm	270±10	40±2	30±5
Roundex 40	1m±2cm	135±6	40±2	30±5
Roundex 50	2m±4cm	180±8	50±2	30±5
Roundex 50	1m±2cm	90±4	50±2	30±5
Roundex 75	2m±4cm	80±4	75±3	35±5
Roundex 90	2m±4cm	56±4	90±4	35±5
Roundex 100	2m±4cm	50±4	100±4	35±5

Color grey/white.

P.I. La Serra II. 25320 Anglesola—Lleida  
Tlf: +34-973308518.

[www.okcompany.com](http://www.okcompany.com) / [infotec@okcompanysa.com](mailto:infotec@okcompanysa.com)



OVERSEAS KONSTELLATION  
COMPANY S.A.

JUNE 2015