

Denso Flashing Tape Primer

Fast-drying primer for the preparation of surfaces

Composition

Denso Flashing Tape Primer is comprised of oxidised bitumen in aromatic hydrocarbon solvent.

Uses

Denso Flashing Tape Primer is used as surface preparation to maintain surface cleanliness prior to the application of Denso Flashing Tape.

Characteristics

Denso Flashing Tape Primer is:

- fast drying,
- easy to apply, and
- improves cathodic disbondment resistance.

Surface Preparation

Surfaces must be clean, dry and free from rust, scale and non-adherent coatings. Preferably, the area will be grit blasted or well wire brushed.

Application

See *Instructions for use* for additional detail. Apply Denso Flashing Tape Primer evenly over the surface using a brush.

Application temperatures: 0°C to +50°C.

Cleaning solvent

Denso Flashing Tape Primer may be cleaned with white spirit.

Availability

Denso Flashing Tape Primer is available in 1 L tins.

Storage conditions

Store all components upright in original packaging in a cool and dry place. Keep away from heat, sparks and open flames.

Waste material

Please avoid or minimise waste wherever possible. Please do not discard waste material, including packaging, in the surrounding environment. Follow all relevant legislation for disposal.

Typical Properties

Colour	Black
Specific Gravity	0.94
Solids Content	59% w/w
Flash Point (c.c)	23°C minimum
Drying Time	10-15 minutes
Surface Coverage	7-8 m ² /L (@ DFT 70-80 µm)
VOC	<440 g/L

Important: Winn & Coales (Denso) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request. Winn & Coales (Denso) Ltd operate a Quality Management System registered to BS EN ISO 9001 (BSI Certificate no. FM01548) and an Environmental Management System registered to BS EN 14001 (BSI Certificate 583748).